

L4: Entry 2 of 4

File: DWPI

Dec 11, 1981

DERWENT-ACC-NO: 1982-A5613E

DERWENT-WEEK: 198203

COPYRIGHT 2003 DERWENT INFORMATION LTD

TITLE: <u>SAW</u> controlled <u>transversal</u> filter - has charge transfer effected by acoustically excitable blade mounted at end of piezoelectric transducer connected to generator

INVENTOR: HENAFF, J

PATENT-ASSIGNEE:

ASSIGNEE CODE FELDMANN M FELDI

PRIORITY-DATA: 1980FR-0012868 (June 10, 1980)

PATENT-FAMILY:

PUB-NO PUB-DATE LANGUAGE PAGES MAIN-IPC

FR 2484150 A December 11, 1981 009

INT-CL (IPC): H01P 1/20

ABSTRACTED-PUB-NO: FR 2484150A

BASIC-ABSTRACT:

The <u>transversal</u> charge transfer filter comprises a semiconductor substrate (10) e.g. p-type silicon coated with a series of parallel electrode strips (14) some of which are gapped with the two portions connected to respective terminal electrodes running the length of the substrate and coupled to respective inputs of a <u>differential</u> amplifier (20). The series is proceded by a charge injection diode (16) and followed by a charge collector diode (18).

Control of charge transfer is effected by a leaf (22) of e.g. niobium and lithium, which can propagate a <u>surface acoustic wave</u>, the leaf having a piezoelectric transducer (24) at one end connected to an a.c. generator (26) and a shock absorber (28) at the other. The leaf is located on the substrate electrodes so that propagation of a <u>surface wave</u> ensures charge displacement in the substrate.

CHOSEN-DRAWING: Dwg.2

TITLE-TERMS: <u>SAW</u> CONTROL TRANSVERSE FILTER CHARGE TRANSFER EFFECT ACOUSTIC EXCITATION BLADE MOUNT END PIEZOELECTRIC TRANSDUCER CONNECT GENERATOR

ADDL-INDEXING-TERMS: